

DECLARATION OF PERFORMANCE

N°: 90125 – CPR – AC1 – 001

1. Unique identification code of the product-type:
Armourbase PRO PLUS
2. Intended use/es:
Flexible sheets for waterproofing - Underlays for discontinuous roofing
3. Manufacturer:
IKO Sales International NV - Truibroek 74 - B-3945 Ham, Belgium
Tel. +32.11.340.120 - Fax. +32.11.340.130 - residential.europe@iko.com - www.ikodop.eu - www.iko.be
4. Authorised representative:
-
5. System/s of AVCP: **System 3**
6. Harmonised standard: **EN 13859-1:2014**
Notified Body: **0071**
7. Declared performances

Essential characteristic	Result	Units	Tolerance	Ref. Norm
Reaction to fire	Class E	-	-	EN 13859-1:2014
Resistance to water penetration before artificial ageing	Class W1	-	-	
Resistance to water penetration after artificial ageing	Class W1	-	-	
Tensile strength in longitudinal direction before artificial ageing	400	N/50mm	± 15%	
Tensile strength in longitudinal direction residual value after artificial ageing	340	N/50mm	± 15%	
Tensile strength in transverse direction before artificial ageing	280	N/50mm	± 15%	
Tensile strength in transverse direction residual value after artificial ageing	224	N/50mm	± 15%	
Elongation longitudinal direction	30 - 50	%	-	
Elongation transverse direction	40 - 60	%	-	
Nail tearing longitudinal direction	150	N	± 15%	
Nail tearing transverse direction	150	N	± 15%	
Flexibility at low temperature	-40	°C	-	
Dangerous Substances (Note 1)	NPD	-	-	

NPD=No Performance Determined

Note 1: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Ham, 09/11/2020
(place and date of issue)

Kurt Kesters – Technical Product Manager
(name and function)

 0071	<h1>Armourbase PRO PLUS</h1>	
	Flexible sheets for waterproofing - Underlays for discontinuous roofing	
20	IKO Sales International NV - Truibroek 74 - B-3945 Ham, Belgium Tel. +32.11.340.120 - Fax. +32.11.340.130 - residential.europe@iko.com - www.ikodop.eu - www.iko.be	
90125 – CPR – AC1 – 001		
EN 13859-1:2014		
Reaction to fire		Class E
Resistance to water penetration before artificial ageing		Class W1
Resistance to water penetration after artificial ageing		Class W1
Tensile strength in longitudinal direction before artificial ageing		400 N/50mm ± 15%
Tensile strength in longitudinal direction residual value after artificial ageing		340 N/50mm ± 15%
Tensile strength in transverse direction before artificial ageing		280 N/50mm ± 15%
Tensile strength in transverse direction residual value after artificial ageing		224 N/50mm ± 15%
Elongation longitudinal direction		30 - 50 %
Elongation transverse direction		40 - 60 %
Nail tearing longitudinal direction		150 N ± 15%
Nail tearing transverse direction		150 N ± 15%
Flexibility at low temperature		-40 °C
Dangerous Substances		NPD